Duct accessories · Access doors

# Duct access doors

Galvanised steel access doors for ductwork. Fit them where fire dampers, coils or filters need to be inspected or cleaned.

## Part numbers

| Part number | Description | Size (mm) | Unit |
|---|---|---|---|
| AS-ADR-295205 | Duct access door 295 × 205 | 295 × 205 face, 245 × 155 neck | Each |
| AS-ADR-430295 | Duct access door 430 × 295 | 430 × 295 face, 380 × 245 neck | Each |

## Key specifications

| | |
|---|---|
| Sizes | 295 × 205 mm and 430 × 295 mm face |
| Material | Galvanised steel |
| Door | Insulated, with rubber seal |

## General

| | |
|---|---|
| Product type | Duct access door |
| Material | Galvanised steel, 0.6 to 0.8 mm |
| Insulation | 22 mm, inside the door |
| Seal | Heat-resistant rubber seal around the door edge |
| Latches | Two turn latches |
| Depth | 25 mm |

## Sizes

| | |
|---|---|
| AS-ADR-295205 | Face 295 × 205 mm, neck 245 × 155 mm |
| AS-ADR-430295 | Face 430 × 295 mm, neck 380 × 245 mm |

## Overview

An access door gives a safe, sealed opening into the duct for inspection and cleaning. Fit one beside fire dampers, coils, filters and other parts that need service.

The door is pressed from 0.6 to 0.8 mm galvanised steel, so it is strong and resists rust. It has 22 mm of insulation inside and a heat-resistant rubber seal around the edge. It closes tight and keeps the air in the duct at temperature. Two turn latches hold it shut.

Two sizes are available. The neck size is the opening you cut into the duct.

## Typical applications

Fire damper inspection · Duct cleaning · Coil and filter service · Commercial ductwork



Specifications may change without notice. Confirm details for your project with Austra Supply before ordering.

**Trade pricing:** send part numbers and quantities to harjot@austrasupply.com or through austrasupply.com/contact.


Specifications may change without notice. Confirm details for your project with Austra Supply before ordering.